

HU-60-1250/HU-60-1255 GAS-FIRED HUMIDAIRE

TUNING (AIR/WATER)	PB	11/13	OPTION	AUXOUT	DIS
	RATE T	0.50/0.60		0 PCT	NA
	I MIN	1.0/0.90		100PCT	NA
	SECUR			CRANGE	NA
SP RAMP	LOCK	MAX	COM	DIGIN1	NONE
	AUTOMA	DISABLE/ENABLE		DIGIN2	NONE
	RN HLD	DISABLE		ComADR	1
	SP SEL	DISABLE		ComSTA	DIS
ACCUTUNE	SP RAMP	DISABLE	ALARMS	IRENAB	DIS
	SP RATE	DISABLE		BAUD	9600
ALGORITHM	FUZZY	DISABLE		TX DLY	1
	ACCUTUNE	DISABLE		A1S1 VAL	NA/5.0
OUT ALG	CONT ALG	PID A		A1S2 VAL	NA
	TIMER	DISABLE		A2S1 VAL	NA
INPUT 1	INP ALG1	NONE		A2S2 VAL	NA
	OUT ALG	CURRENT		A1S1 TYPE	NA/DEV
INPUT 2	CRANGE	4-20	DISPLAY		
	IN1 TYPE	J L		A1S2 TYPE	NONE
	XMITTER1	NA		A2S1 TYPE	NONE
	IN1 HI	770		A2S2 TYPE	NONE
CONTROL	IN1 LO	20		A1S1 HL	LO
	RATIO 1	1.0		A1S1 EV	NA
	BIAS IN1	0.0		A1S2 HL	NONE
	FILTER 1	2		A1S2 EV	NA
INPUT 2	BURNOUT1	UP		A2S1 HL	NONE
	IN2 TYPE	NA		A2S1 EV	NA
	XMITTER2	NA		A2S2 HL	NONE
	IN2 HI	NA		A2S2 EV	NA
CONTROL	IN2 LO	NA		AL HYST	0.1
	RATIO 2	NA		ALM OUT1	NO LAT
	BIAS IN2	NA		BLOCK	DISABLE
	FILTER 2	NA		DECIMAL	NONE
CONTROL	BURNOUT2	NA		TEMPUNIT	DEG F
	PV SOURC	INPUT 1		PWR FREQ	60 HZ
	PID SETS	1 ONLY		RATIO 2	DISABLE
	LSP'S	1 ONLY		LANGUAGE	ENGLISH
CONTROL	RSP SRC	NONE			
	SP TRACK	NONE			
	PWR MODE	ALSP			
	SP HILIM	155			
CONTROL	SP LOLIM	95			
	ACTION	REVERSE			
	OUTRATE	DISABLE			
	OUTHILIM	100.0			
CONTROL	OUTLOLIM	0.0			
	I HILIM	100.0			
	I LOLIM	0.0			
	DROPOFF	0.0			
CONTROL	FAILMODE	NO LAT			
	FAILSAFE	0.0			
	MAN OUT	0.0			
	AUTO OUT	40.0/0.0			
CONTROL	PB OR GAIN	PB PCT			
	MIN OR RPM	MIN			