

HU-60-1250/HU-60-1255 GAS-FIRED HUMIDAIRE

TUNING (AIR/WATER)

PROP BD	11/13
RATE MIN	0.50/0.60
RSET MIN	1.0/0.90
SECURITY	
LOCKOUT	MAX
AUTO MAN	DISABLE/ENABLE
SP SEL	DISABLE
RUN HOLD	DISABLE

SP RAMP

SP RAMP	DISABLE
SP RATE	DISABLE

ACCUTUNE

FUZZY	DISABLE
ACCUTUNE	DISABLE

ALGORITHM

CONT ALG	PID A
TIMER	DISABLE
INP ALG1	NONE

OUT ALG

OUT ALG	CURRENT
---------	---------

INPUT 1

IN1 TYPE	J TC L
XMITTER1	NA
IN1 HI	770
IN1 LO	20
RATIO 1	1.0
BIAS IN1	0.0
FILTER 1	1
BURNOUT1	UP

INPUT 2

IN2 TYPE	NA
XMITTER2	NA
IN2 HI	NA
IN2 LO	NA
RATIO 2	NA
BIAS IN2	NA
FILTER 2	NA
BURNOUT2	NA

CONTROL

PV SOURC	INPUT 1
PID SETS	1 ONLY
LSP'S	1 ONLY
RSP SRC	NONE
SP TRACK	NONE
PWR MODE	ALSP
SP HILIM	155
SP LOLIM	95
ACTION	REVERSE
OUTRATE	DISABLE
OUTHILIM	100.0
OUTLOLIM	0.0
I HILIM	100.0
I LOLIM	0.0
DROPOFF	0.0
FAILMODE	NO LAT
FAILSAFE	0.0
MAN OUT	0.0
AUTO OUT	40.0/0.0
PB OR GAIN	PB PCT
MIN OR RPM	MIN

ALARMS

A1S1 VAL	NA/5.0
A1S2 VAL	NA
A2S1 VAL	NA
A2S2 VAL	NA
A1S1 TYPE	DEV
A1S2 TYPE	NONE
A2S1 TYPE	NONE
A2S2 TYPE	NONE
A1S1 HL	LO
A1S1 EV	NA
A1S2 HL	NONE
A1S2 EV	NA
A2S1 HL	NONE
A2S1 EV	NA
A2S2 HL	NONE
A2S2 EV	NA
AL HYST	0.1
ALM OUT1	NO LAT
BLOCK	DISABLE

DISPLAY

DECIMAL	XXXX
TEMPUNIT	DEG F
PWR FREQ	60 HZ
RATIO 2	DISABLE
LANGUAGE	ENGLISH

2/5/99